

Technical Data

Product: SOGEVAC SV 25 B - without gas ballast valve
Part-No.: 960255

Inlet connection:	G 3/4" + G 1/2" Inside thread	
Outlet connection:	G 3/4" Inside thread	
Nominal pumping speed at 50 Hz:	26.0 m ³ /h	15.3 cfm
Nominal pumping speed at 60 Hz:	31.0 m ³ /h	18.3 cfm
Pumping speed at 50 Hz:	22.5 m ³ /h	13.3 cfm
Pumping speed at 60 Hz:	25.0 m ³ /h	14.7 cfm
Ultimate partial pressure without gas ballast:	≤ 0.5 mbar	≤ 0.4 Torr
Ultimate total pressure without gas ballast:	≤ 0.5 mbar	≤ 0.4 Torr
Ultimate total pressure with gas ballast:	- - -	
Water vapor tolerance at 50 Hz:	- - -	
Water vapor tolerance at 60 Hz:	- - -	
Water vapor capacity at 50 Hz:	- - -	
Water vapor capacity at 60 Hz:	- - -	
Operating fluid:	LVO 120	
Operating fluid capacity:	0.5 l	0.53 qt
Noise level to DIN 45 635		
without gas ballast:	64 - 67 dB(A)	
with gas ballast:	- - -	
Mains connection:	1-ph, 230 V, 50/60 Hz	
Motor rating at 50 Hz:	0.9 kW	1.2 HP
Motor rating at 60 Hz:	1.1 kW	1.5 HP
Rotation speed at 50 Hz:	3.000 min ⁻¹	3.000 rpm
Rotation speed at 60 Hz:	3.600 min ⁻¹	3.600 rpm
Motor protection rating:	IP 55-F	
Admissible ambient temperature:	+12 to +40°C	+54 to +104°F
Dimensions:	see dimension sheet	
Weight:	≈ 27.0 kg	≈ 60.0 lbs

Technical data are subject to change